14-Slot Rackmount Chassis Datasheet

MODELS: TL-MC1400

MC210CS
MC200CM
MC112CS
MC220L
TL-MC1400
MC111CS
MC100CM
MC110CS

Overview

The TL-MC1400 14-Slot Rackmount Chassis is specially designed to accommodate 14 tp-link's Media Converters for central power supply, saving space and power cables. Continuous operation is of great importance to fiber communication, so the chassis is equipped with optional redundant power supply and Hot-Swapping function which allows installing/removing the converter without powering off the chassis. Moreover, to stabilize the performance and extend the lifetime, two cooling fans are installed internally. Together with MC series Gigabit / Fast Ethernet media converters, TL-MC1400 is the ideal solution for your media conversion network.

Highlights

- 14 bays to house up to 14 media converters*

- Optional redundant power supply to ensure non-stop reliable operation

- Hot-Swappable; easy & quick replacement of converter

- Standard 19-inch rack-mountable, 2U height

- Mounted two cooling fans for better ventilation

- Offers over-voltage and over-current protections

* For tp-link Media Converters, TL-MC1400 supports MCXXX ver:2.0 and above, not ver:1.0."

Specifications

Product Picture	
AC Power Supply	Input: 100-240V~50/60Hz 3.0A(Max) Output:+12VDC, 8.5A(Max)
Fan Quantity	2
Dimensions (W*D*H)	19.0*12.2*3.4in.(482*309*86) Standard 19-Inch, 2U height
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉) Storage Temperature: -40℃~70℃ (-40℉~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity:5%~90% non-condensing

tp-link