Yealink

Easy Audio and Visual Communication

The Yealink SIP-T58W Pro with camera is a simple-to-use smart business phone that provides an enriched HD audio and video calling experience for business professionals. This smart business phone enables productivity-enhancing visual communication with the ease of a standard phone. Pro means that this phone supports Yealink Bluetooth handset BTH58, with which users are free to move around when on a call - no more missed calls when they leave their desk. With a range of up to 10 meters (30 feet), the Yealink Bluetooth handset offers more office flexibility for users. Based on the Android 9.0 operating system, the SIP-T58W Pro with camera adopts a new user interface, which is more concise and business, greatly improving user's work efficiency. Furthermore, the SIP-T58W Pro with camera integrates with IP video intercom systems from major vendors in the market, delivering true cost-efficiency to customers.



Wireless

Handset

HD

720P



Android 9.0

Key Features and Benefits

also adds flexibility for office workers.

A Better User Experience with Android 9.0 System





7-inch Multi-

touch Screen



Corded-Cordless

Phone



Yealink's SDK



HD Audio





HD Video

Enjoy Wireless Freedom

Built-in Built-in Wi-Fi Bluetooth



DoorPhone USB 2.0 Features

High Security

Runs Android 9.0

- 7 inch (1024 x 600) capacitive adjustable touch screen
- Supports Yealink Bluetooth Handset BTH58
- 720p30 HD video
- Optimal HD audio, Yealink Noise Proof Technology
- Yealink's SDK (Software Development Kit)
- DoorPhone Features

(Preview, One-button Open, Monitoring)

- · Built-in Bluetooth 4.2 and Dual Band 2.4G/5G Wi-Fi
- · 2 x USB 2.0 ports for USB headset, media and storage applications
- Opus Codec support
- · Up to 16 SIP accounts
- · Up to 3-party video conferencing
- Up to 10-party video/audio mixed conferencing (up to 2 video calls)
- Dual-port Gigabit Ethernet, supports PoE
- Wall mountable
- Supports up to 3 Expansion Module EXP50
- Supports Yealink/Unify Square Device Management Platform

business, and easier to use.

HD Audio and HD Video

The Yealink SIP-T58W Pro with camera includes the latest version of Yealink Optimal HD Voice technologies, including the Yealink Noise Proof Technology and supports the Opus codec, which helps maximize the acoustic performance of the phone's handset, headset and especially the speakerphone. And its hearing aid compatible (HAC) handset helps the person who is with hearing loss to hear the voice more clearly. With the dynamic, removable five-megapixel HD camera CAM50, you can connect into video conferences directly from your desk. The camera parameters such as exposure, noise point, definition, white balance, and field of view are better than those of the previous generation phone.

The Yealink SIP-T58W Pro with camera supports the brand-new Bluetooth wireless handset BTH58, providing up to 17 hours of talk time and 46 hours of standby time, allowing the user to

leave the desk and continue talking, not only provides crystal clear voice communications but

Based on Android 9.0, the Yealink SIP-T58W Pro with camera not only inherits the advantages

of the previous generation, but is also compatible with more third-party apps, bringing more convenience to users. Administrators can easily install additional Android applications to im-

prove collaboration and productivity. The Yealink's newly designed user interface is more fluent,

Improved Security Performance

The Yealink SIP-T58W Pro with camera adopts Arm TrustZone technology, which can greatly improve the security of various ARM-based data and applications, and establish a reliable security defense system. The Android version has been upgraded to add firmware and data encryption for more security. Moreover, the phone's authority management and control is stricter and more specific.

Yealink

Specifications

Only the administrator can install/uninstall apps via

Supports Yealink Device Management Platform (YMDP/YMCS)

Proxy mode and peer-to-peer SIP link mode

Time and date synchronization using SNTP

QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP

AES encryption for configuration file (AES256)

GARP (Generic Attribute Registration Protocol)

External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output

Dimension (W*D*H*T): 259.4mm*220mm*239m-

Operating temperature: 0~40°C (+32~104°F)

Yealink SIP-T58W Pro with camera IP phone

Wired handset with handset cord (Optional) BTH58 Bluetooth handset

Giftbox size: 324 mm*293 mm*128 mm

Carton Meas: 680 mm*303 mm*342 mm

broadsoft **3**CX metaswitch

REACH ISO 9001

USB Flash Drive

Web: www.yealink.com

USB output currency: 5V === 500mA

Power consumption (PoE): 3.3W~9W

Operating humidity: 10~95%

Power consumption (PSU): 2.5W~7.5W

Digest authentication using MD5/MD5-sess

Supports Unify Square Device Management Plat-

autóp

IPv4/IPv6

• SRTP

٠

Setup Assistant wizard

• SIP v1 (RFC2543), v2 (RFC3261)

· Call server redundancy supported

UDP/TCP/DNS-SRV (RFC 3263)

Transport Layer Security (TLS1.3)

OpenVPN, IEEE802.1X, L2TP VPN

HTTPS certificate manager

WPA2/WPA3

Secure boot

m*42.6mm

Package Features

Handset:

- Stand

Compliance

Package content:

Ethernet Cable

Qty/CTN: 5 PCS

N.W/CTN: 8.880 kg

G.W/CTN: 9.558 kg

(E 💩 FC <u>hac</u> 🖉

USB 2.0

Yealink CAM50 camera

Quick Start Guide Power Adapter (Optional)

Other Physical Features

Color: Classic Grey

Wall mountable (optional)

Adb encryption authenticated

NAT traversal: STUN mode

· IP assignment: static/DHCP

HTTP/HTTPS web server

Network and Security

Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Acoustic Shield, Noise Proof
- Smart Noise Filtering
- Audio codec: Opus, G.722, PCMA, PCMU, G.729, G.729A, G.726, G.723.1, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Video Features

- Video codec: H.264 High Profile, H.264, VP8
- Video quality: 720P (1280x720)-30fps (≥ 512 kbps)
- Yealink CAM50 camera:
- 5 mega-pixel
- Plug and play - Adjustable
- With privacy shutter and LED indicator
- Vertical tilt angle adjustable: 47±39
- Field of view (FOV): 75°±5°
- · Self view (local video preview)

Display and Indicator

- LCD screen:
- 7" 1024 x 600 capacitive adjustable touch screen - Vertical tilt angle adjustable: 48°
- · 5 points multi-touch surface
- Screensaver and Wallpaper
- LED for call and message waiting indication
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name, number and photo

Android bundled Applications

- FileManager/Email/Calendar/Camera/Gallery/ Recorder/Calculator/Browser/Message
- Third party Android application support

Phone Features

- Yealink's SDK (Software Development Kit)
- 16 SIP accounts
- Call hold, call forward, call waiting, call transfer
- One-touch speed dial, hotline, mute, DND
- Group listening, emergency call
- Redial, call return, auto answer
- Direct IP call without SIP proxy
- Ring tone select/import/delete
- Set date time manually or automatically
- Dial plan, action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- 3-party video conferencing
- 10-party audio/video mixed conferencing (up to two video calls)
- Data import/export via Bluetooth, email, etc.
- DoorPhone features: Preview, One-button Open, Monitoring
- USB/Bluetooth connectivity to Yealink CP900/CP700 Management speakerphone, USB connectivity to Yealink UH36 headset - Basic functions: Answer/end, call mute
- Enhanced function: audio optimization, redial, call hold, volume synchronization, multiple calls control

PC

8

PC

YEALINK NETWORK TECHNOLOGY CO., LTD.

6

Interne

Internet

DC5V

- Analog PSTN calls via CPN10
- Wireless Access Point (AP mode)

Corded-Cordless Phone (via DECT Dongle DD10K)

- Up to 4 DECT cordless handsets
- Up to 4 concurrent calls
- Support Yealink W73H/W53H/W56H/W59R/DD Phone/CP930W
- Slave Handset for Master Deskset

IP-PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Remote office, hot desking, intercom, paging
- Call completion
- Message Waiting Indicator (MWI)
- Voice mail, call park, call pickup
- Music on hold
- · Call recording

Directory

- Local phonebook up to 1000 entries
- Block list
- XML/LDAP remote phonebook
- Google contacts
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded .

Feature keys

- 27 one-touch DSS keys
- 7 feature keys: hold, transfer, message, headset, mute, redial, speakerphone
- Volume control keys
- Illuminated mute/headset/hands-free speakerphone kev

Interface

- · Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 3
- Built-in dual band Wi-Fi:
- Network standard: IEEE802.11a/b/g/n
- Frequency range: 2.4GHz/5.0GHz
- Built-in Bluetooth 4.2 for - Bluetooth Handset BTH58
- Bluetooth headsets
- Pairing mobile devices
- Simultaneous connection of one headset and one mobile phone
- 1 x USB 2.0 port (on the top of the phone) for: Yealink CAM50 camera
- 1 x USB 2.0 port (on the rear of the phone) for: - USB flash drive
- Wired/wireless USB headset
- Color-screen expansion modules
- Wireless Headset Adapter EHS40
- 1 x Security lock port

Reset to factory, reboot

- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port
- · Supports up to 3 color-screen expansion modules

· Configuration: browser/phone/auto provision

Phone lock for personal privacy protection

Package tracing export, system log

Auto provision via FTP/TFTP/HTTP/HTTPS

Auto provision with PnP, Zero-sp-touch, TR-069

•

Email: sales@yealink.com



About Yealink

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

Copyright

Copyright © 2021 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD. Web: www.yealink.com Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District, Xiamen, Fujian, P.R.C Copyright©2021 Yealink Inc. All rights reserved.