



AX1800 Wi-Fi 6 Bluetooth 5.4 PCle Adapter

Model: MA70XE

Highlights

- 1201 Mbps + 574 Mbps Dual-Band Wi-Fi[†]
- Powerful Wi-Fi 6 Chipset
- Fixed High-Performance Antennas
- Armed with Bluetooth 5.4
- WPA3 for Overall Security Protection*





Features

Upgrade Your PC to Wi-Fi 6

Wi-Fi 6 features 1024-QAM, OFDMA, and MU-MIMO, delivering faster, more efficient, and reliable data transmissions to meet the demand for high-performance wireless experiences.[‡]



Super Stable Bluetooth 5.4

MA70XE upgrades your PC with cutting-edge Bluetooth 5.4, designed for enhanced stability, broader compatibility, and faster transmission speeds. Simply connect your Bluetooth devices to your computer and enjoy with ease.**





Boost Wireless Range

Two high-performance antennas reach your router from farther away with more precise directional range, sustaining faster and more stable wireless connections.



Overall Security Protection

The latest security standard, WPA3, provides improved comprehensive Wi-Fi protection to defend your devices and private information against brute-force attacks.*



Specifications

Wireless

Wireless Standards

Compatible with 11ax/ac/a/b/g/n Wi-Fi standards[†]

Signal Rate

1201 Mbps on 5 GHz 574 Mbps on 2.4 GHz

EIRP

5 GHz: 20dBm(FCC) /15dBm(CE) (EIRP) 2.4 GHz: 20dBm(FCC) / 16dBm(CE) (EIRP)

Hardware

Antennas

2× Fixed High-Performance Omni-Directional Antennas

Dimensions

 $226.3 \times 120.8 \times 21.5 \text{ mm}$ (8.9 × 4.8 × 0.85 in)

Reception Sensitivity

5 GHz:

11ax HE80 MCS0: -90 dBm 11ax HE80 MCS11: -59 dBm 11a 54Mbps: -77 dBm

11ac VHT80 MCS0: -92dBm 11ac VHT80 MCS9: -64dBm

2.4 GHz:

11ax HE40 MCS0: -91 dBm 11ax HE40 MCS11: -60 dBm

11g 54Mbps: -76 dBm 11n HT40 MCS7: -72dBm

Software

Working Mode

Infrastructure mode

Wireless Security

WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK*



Specifications

Others

Environment

Operating Temperature: 0°C~40°C (32°F~104°F)

Operating Humidity: 10%~90% Non-Condensing

Storage Humidity: 5%~90% Non-Condensing

Package Contents

AX1800 Wi-Fi 6 Bluetooth 5.4 PCle Adapter (MA70XE)

Bluetooth Header Cable

Quick Installation Guide

Resource CD

Certification

FCC, CE, RoHS

System Requirements

Windows 11/10 (64-bit)⁴

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2025 MERCUSYS. All rights reserved.

'Maximum wireless signal rates are the physical rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage, and number of connected devices are not guaranteed and will vary as a result of network conditions, AP limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and AP location.

*Use of Wi-Fi 6 and features including OFDMA, MU-MIMO, 1024-QAM, or HE160 requires APs to also support the corresponding features.

AFunctionality of MA70XE may be restricted on some computing systems and platforms. Please try to update the device's driver for feature compatibility.

\$602.11 ax enables 1201 Mbps maximum theoretical data rates on 5 GHz, 1.4× faster than 802.11ac (867 Mbps on 5 GHz) and nearly 2.7× faster than baseline 1×1 ac Wi-Fi (433 Mbps on 5 GHz) as documented in IEEE 802.11 wireless standard specifications, and require the use of similarly configured 802.11ax wireless network routers.

*Use of WPA3 requires APs to also support the corresponding feature.

^{**}Several new features were introduced in the Bluetooth Core Specifications 5.0, 5.3, and 5.4, including 2× faster speed and 4× broader coverage compared with Bluetooth 4.2.