

Highlights

Multi-Gigabit Ethernet Connection

Delivers fast 2.5 Gbps performance using existing cabling, suitable for Wi-Fi 6 network deployments

10G Uplink Connections

Two 10-Gigabit Ethernet or SFP+ uplink ports allow for additional connections to a storage device or uplink network

Power over Ethernet

PoE+ (30W) or PoE++ (60W) options to simultaneously power multiple types of PoE devices with various power draw requirements



Smart Managed Switches

DMS-1250 Series

Features

PoE Functionality¹

- IEEE 802.3bt or IEEE 802.3af/at compliant
- Up to 120 W or 240 W PoE budget
- Fast and perpetual PoE

Enhanced Security Features

- Access Control Lists (ACLs)
- D-Link Safeguard Engine helps the CPU resist broadcast/multicast/unicast flooding
- Port Security supports up to 64 MAC addresses per port

Smart Fan Design

- 5-speed smart fan design automatically adjusts according to device operating temperature
- Quiet mode or noiseless Fan Off mode

Intuitive Management

- Multi-lingual Web UI
- Full command line support via console port³
- D-Link Nuclias Connect and D-Link Nuclias Connect Hub (version 1.3.0 or later)
- Built-in SNMP MIB for remote NMS (D-View 8)

Advanced Features

- Static routing
- Auto-surveillance and Voice VLAN
- Dual software images
- Dual configuration files
- 6kV surge protection on all 2.5-Gigabit Ethernet access ports

Limitless Applications

- Ideal for SMB and MDU applications
- Small footprint (-10SPL) to fit inside structured wiring media enclosures

The DMS-1250 Series is D-Link's newest family of Multi-Gigabit Ethernet smart switches. It provides multi-Gigabit connectivity, Power over Ethernet (PoE) capability, multiple management interfaces and advanced layer 2 features. The DMS-1250 Series provides a high-performance solution to expand your network and adapts to your business needs.

Multi-G Speeds for Wi-Fi 6 Networks

The DMS-1250 Series provides full 2.5 Gbps Ethernet ports to significantly upgrade network performance with increased bandwidth suitable for Wi-Fi 6 applications such as high-speed streaming environments. It also provides additional 10 Gbps Ethernet ports and SFP+ ports for high-speed uplink connections and increase overall efficiency of data network.

PoE+ Availability on All Ports

The DMS-1250-10SP and DMS-1250-12TP offer eight IEEE 802.3at PoE ports to provide up to 240 W PoE power budget to power devices such as video phones, cameras, and Wi-Fi APs to fulfill a wide range of business needs. The DMS-1250-10SPL switch has two IEEE 802.3bt PoE ports and six IEEE802.3at PoE ports with 120 W PoE budget. The 802.3bt ports can provide up to 60 W per port and allow connections for high-power devices. PoE models also support innovative PoE functions such as Perpetual PoE, which delivers uninterrupted power to connected powered devices (PD) even when the power sourcing equipment (PSE) switch is booting. Fast PoE enables the switch to supply power to connected endpoint devices in a relatively short time without waiting for the operating system to boot up. Additionally, an extended Link Layer Discovery Protocol (LLDP) automatically negotiates and manages the power feed to IEEE 802.3at PoE+ and 802.3bt PoE++ powered devices for optimal power distribution.

Enhance Your Network Security

The D-Link's innovative Safeguard Engine™ helps protect the switches against traffic flooding caused by malicious attacks. 802.1X port-based and host-based authentication allows clients to be authenticated through external RADIUS servers and can provide a more secure network connection. The Access Control List (ACL) feature can help enhance network security and better control access between internal networks. The DHCP server screening feature can filter DHCP replies on unauthorized ports to prevent them from being assigned an IP address, which provides an additional security mechanism.

DMS-1250 Series Smart Managed Switches

Intelligent Fan Operation

The DMS-1250-10SP and DMS-1250-12TP PoE models have built-in internal fans which can automatically start working to prevent the device from overheating. The fan speed will be gradually adjusted between 5 levels of cooling according to the operating temperature of the switch. Administrators can also configure the operation state of internal fans through Web UI or command line interface (CLI). The switch fans can be manually set to Fan Off mode or Quiet mode if the ambient temperature or PoE load do not exceed the critical level.

Versatile Management Tools

The DMS-1250 Series supports various management tools to adapt to users' different needs. D-Link Nuclias Connect (DNC) and D-Link Nuclias Connect Hub (DNH) can discover multiple D-Link devices and allow you to manage and configure the settings of the discovered devices. The DMS-1250 Series can also be managed by D-View 8, a central network management system. Full command line interface (CLI) is supported and IT personnel can directly configure the device through the console port³ or via Telnet. SNMP allows for the central management of network assets, remote configuration, and logging functions.

Enhanced 6kV Surge Protection

The DMS-1250 Series switches offer enhanced 6kV surge protection on all 2.5-Gigabit Ethernet access ports. The 6kV surge protection helps shield the switches against sudden electrical surges, such as lightning strikes or unstable electrical current. Built-in 6kV surge protection helps reduce the chances of equipment being damaged from electrical surges, and effectively lowers maintenance costs by minimizing the need for expensive repairs and replacement.

Advanced L2/L2+ Features

The DMS-1250 series switches provides configurable L2 network features like VLANs, Quality of Services, Spanning Tree Protocol. The Auto Surveillance VLAN (ASV) and Voice VLAN function can guarantee the quality of video and voice services through the individual VLAN with higher priority. The Differentiated Service Code Point (DSCP) markings on Ethernet packets enable different levels of service to be assigned to network traffic. These voice and video packets thus can take precedence over other packets. It also supports Static route, IPv4/IPv6, LACP link aggregation and IGMP snooping, which can meet the needs of most business applications.

DMS-1250 Series Smart Managed Switches

| Technical Specifications | | | | |
|---------------------------------------|--|---|---|---|
| Model Number | DMS-1250-10S | DMS-1250-10SP | DMS-1250-12TP | DMS-1250-10SPL |
| Hardware Version | A1 | | | |
| General | | | | |
| Interfaces | <ul style="list-style-type: none"> • 8 x 100/1000/2.5GBASE-T ports • 2 x 10G SFP+ ports | <ul style="list-style-type: none"> • 8 x 100/1000/2.5GBASE-T PoE ports • 2 x 10G SFP+ ports | <ul style="list-style-type: none"> • 8 x 100/1000/2.5GBASE-T PoE ports • 2 x 100/1000/2.5G/5G/10GBASE-T ports • 2 x 10G SFP+ ports | <ul style="list-style-type: none"> • 8 x 100/1000/2.5GBASE-T PoE ports • 2 x 10G SFP+ ports |
| Port Standards | <ul style="list-style-type: none"> • IEEE 802.3u 100BASE-TX • IEEE 802.3ab 1000BASE-T • IEEE 802.3bz 2.5GBASE-T and 5GBASE-T • IEEE 802.3an 10GBASE-T • IEEE802.3ae 10G Ethernet over fiber • IEEE802.3z 1000BASE-X • IEEE 802.3az Enerby-Efficient Ethernet (EEE) <ul style="list-style-type: none"> • IEEE 802.3af/at PoE • IEEE 802.3bt PoE | | | |
| Network Cables | <ul style="list-style-type: none"> • UTP Cat. 5e above cables for 2.5G/5GBASE-T (max 100m) • UTP Cat. 6A above cables for 10GBASE-T (max 100m) | | | |
| Media Interface Exchange | Auto MDI/MDIX | | | |
| Performance | | | | |
| Switching Capacity | 80 Gbps | 80 Gbps | 120 Gbps | 80 Gbps |
| Transmission Method | Store-and-forward | | | |
| MAC Address Table | 16K | | | |
| Static MAC Addresses | 256 entries | | | |
| Packet Forwarding Rate | 59.53 Mpps | 59.53 Mpps | 89.29 Mpps | 59.53 Mpps |
| Packet Buffer Memory | 12 Mbits | | | |
| Flash Memory | 32 MB | | | |
| DRAM Size | 512 MB | | | |
| PoE | | | | |
| PoE Standard | N/A | IEEE 802.3af/at (30W) | IEEE 802.3af/at (30W) | IEEE 802.3bt (60W) IEEE 802.3af/at (30W) |
| PoE Capable Ports | N/A | 8 | 8 | Port 1-2: 802.3bt ports Port 3-8: 802.3at ports |
| PoE Power Budget | N/A | 240 W | 240 W | 120 W |
| LEDs | | | | |
| Power (per device) | ✓ | | | |
| Link/Active/Speed (per RJ-45 port) | ✓ | | | |
| Link/Active/Speed (per 10G SFP+ port) | ✓ | | | |
| PoE Max and PoE Status ¹ | ✓ | | | |

DMS-1250 Series Smart Managed Switches

| Physical | | | | |
|---------------------------|---|---------------------|--------------------|-------------------------|
| Power Input | 100 to 240 V AC 50/60 Hz | | | DC 54V / 2.78A |
| Surge Protection | <ul style="list-style-type: none"> • IEEE61000-4-5 surge protection compliance • 6kV surge protection on all 2.5-Gigabit Ethernet ports | | | |
| Fan | Fanless | 2 internal fans | 2 internal fans | Fanless |
| Operating Temperature | -5 to 50°C (23 to 122°F) | | | 0 to 40°C (32 to 104°F) |
| Storage Temperature | -20 to 70°C (-4 to 158°C) | | | |
| Operating Humidity | 0% to 95% relative humidity | | | |
| Storage Humidity | 0% to 95% relative humidity | | | |
| Maximum Power Consumption | 13.58 W | 287.58 W (PoE on) | 289.74 W (PoE on) | 147 W (PoE on) |
| Dimensions (L x W x H) | 330 x 200 x 44 mm | 330 x 200 x 44 mm | 440 x 210 x 44 mm | 210 x 210 x 44 mm |
| Weight | 1.877 kg (4.14 lbs) | 2.377 kg (5.24 lbs) | 3.24 kg (7.14 lbs) | 1.34 kg (2.95 lbs) |
| Certifications | | | | |
| Safety | CB, UL, BSMI | | | |
| EMI | CE Class A, VCCI Class A, FCC Class A, IC, BSMI, RCM | | | |
| Software | | | | |
| L2 Features | <ul style="list-style-type: none"> • MAC Address Table <ul style="list-style-type: none"> • 16K entries • IGMP Snooping <ul style="list-style-type: none"> • IGMP v1/v2/v3 awareness • Supports 256 IGMP groups • IGMP per VLAN • Supports IGMP Snooping Querier • MLD snooping v1/v2 awareness (256 groups) • Loopback Detection • 802.3ad Link Aggregation: <ul style="list-style-type: none"> • Supports maximum 8 groups per per device and 8 ports per group • LLDP • LLDP-MED • Jumbo Frame <ul style="list-style-type: none"> • Up to 12,000 bytes • Spanning Tree Protocol <ul style="list-style-type: none"> • 802.1D STP • 802.1w RSTP • 802.1s MSTP • Flow Control <ul style="list-style-type: none"> • 802.3x Flow Control • HOL Blocking Prevention • Port Mirroring <ul style="list-style-type: none"> • One-to-One • Many-to-One • Supports Mirroring for Tx/Rx/Both • Multicast Filtering <ul style="list-style-type: none"> • Forwards all registered groups • Filters all unregistered groups • Auto MDI/MDIX • PD-Alive • DDM support for optics | | | |
| VLAN | <ul style="list-style-type: none"> • 802.1Q • VLAN Group <ul style="list-style-type: none"> • Max. 4094 static VLAN groups • Configurable VID from 1 - 4094 • Asymmetric VLAN • Auto Voice VLAN • Auto Surveillance VLAN | | | |
| Quality of Service (QoS) | <ul style="list-style-type: none"> • 802.1p Quality of Service • 8 queues per port • Queue Handling <ul style="list-style-type: none"> • Strict • WFQ • Weighted Round Robin (WRR) • Bandwidth Control <ul style="list-style-type: none"> • Port-based (ingress/egress, min granularity 10/100/1000 is 16 Kbps) • QoS based on: <ul style="list-style-type: none"> • 802.1p priority queues • DSCP | | | |
| L3 Features | <ul style="list-style-type: none"> • IP interface <ul style="list-style-type: none"> • Supports IPv4 interface • Supports IPv6 interface • IPv6 Neighbor Discovery (ND) • Static route <ul style="list-style-type: none"> • 128 IPv4 static route entries • 64 IPv6 static route entries | | | |

DMS-1250 Series Smart Managed Switches

| | | |
|---------------------------|--|--|
| Access Control List (ACL) | <ul style="list-style-type: none"> • Max. 50 access lists • Max. 768 entries shared by IPv4 and MAC • Max. 384 entries for IPv6 • Each rule can only be associated with a single port • ACL based on <ul style="list-style-type: none"> • MAC address <ul style="list-style-type: none"> • 802.1p priority • VID • Source/destination IP address wildcard • EtherType mask • IP address <ul style="list-style-type: none"> • Source/destination IP address wildcard • DSCP • Protocol type • TCP/UDP port number | <ul style="list-style-type: none"> • IPv6 address <ul style="list-style-type: none"> • Source/destination IP address prefix length • DSCP • Protocol type • TCP/UDP port number • IPv6 traffic class |
| Security Features | <ul style="list-style-type: none"> • Broadcast/Multicast/Unicast Storm Control • D-Link Safeguard Engine • Traffic segmentation • TLS v1.3 • DoS attack prevention • Port Security <ul style="list-style-type: none"> • Supports up to 64 MAC addresses per port | <ul style="list-style-type: none"> • DHCP Server Screening • IP-MAC-Port Binding (Smart Binding) <ul style="list-style-type: none"> • ARP Inspection <ul style="list-style-type: none"> • Max. 64 entries • DHCP Snooping • AAA support for RADIUS/TACACS+ • Password encryption |
| AAA | <ul style="list-style-type: none"> • 802.1X Authentication <ul style="list-style-type: none"> • Supports local/RADIUS database • Supports port-based access control • Supports host-based access control • Supports EAP, OTP, TLS, TTLS, PEAP | <ul style="list-style-type: none"> • IPv6 RADIUS server • Support MD5 authentication |
| OAM | <ul style="list-style-type: none"> • Cable diagnostics | <ul style="list-style-type: none"> • Factory reset |
| Management | <ul style="list-style-type: none"> • Web-based GUI • Full CLI • Telnet Server • TFTP Client • Auto MDI/MDIX • SNMP <ul style="list-style-type: none"> • Supports v1/v2c/v3 • SNMP Trap • Backup/upgrade firmware • Smart Wizard • Upload/download configuration file • BootP/DHCP Client | <ul style="list-style-type: none"> • System Log • SNMP • ICMP v6 • IPv4/v6 Dual Stack • DHCP Auto Configuration • Time setting <ul style="list-style-type: none"> • SNMP • RMONv1 • Trusted host • Dual image • Dual configuration • Command logging |
| Green Technology | <ul style="list-style-type: none"> • Power Saving by: <ul style="list-style-type: none"> • Link Status • Time-based PoE: PoE ports can be turned on/off by port or system through schedule | <ul style="list-style-type: none"> • Port shut off |
| MIBs | <ul style="list-style-type: none"> • RFC1212 Console MIB Definitions • RFC1213 MIBII • RFC1215 MIB Traps Convention • RFC1493 Bridge MIB • RFC1157, RFC2573, RFC2575, RFC2576 SNMP MIB • RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418 SNMPv2 MIB • RFC271, RFC1757, RFC2819 RMON MIB • RFC2021 RMONv2 MIB • RFC1398, RFC1643, RFC1650, RFC2358, RFC2665 Ether-like MIB | <ul style="list-style-type: none"> • RFC2674 802.1p MIB • Interface Group MIB • RFC2618 RADIUS Authentication Client MIB • RFC4022 MIB for TCP • RFC4113 MIB for UDP • RFC2620 RADIUS Accounting Client MIB • Private MIB • PoE MIB • DDP MIB • LLDP-MED MIB |
| RFC Standards | <ul style="list-style-type: none"> • RFC791 IP • RFC768 UDP • RFC793 TCP • RFC792 ICMPv4 • RFC2463, RFC4443 ICMPv6 • RFC826 ARP • RFC1321, RFC2284, RFC2865, RFC2716, RFC3580 Extensible Authentication Protocol (EAP) | <ul style="list-style-type: none"> • RFC2573 SNMP Applications • RFC2461, RFC4861 Neighbor Discovery for IPv6 • RFC2462, RFC4862 IPv6 Stateless Address Auto-configuration (SLAAC) • RFC2464 IPv6 over Ethernet and definition • RFC4291 IPv6 Addressing Architecture • RFC2893, RFC4213 IPv4/IPv6 dual stack function |

DMS-1250 Series Smart Managed Switches

| Order Information | |
|----------------------------|--|
| DMS-1250-10S | Multi-Gigabit Smart Switch with 8-port 2.5GBASE-T and 2-port 10G SFP+ |
| DMS-1250-10SP | Multi-Gigabit Smart Switch with 8-port 2.5GBASE-T PoE and 2-port 10G SFP+ |
| DMS-1250-12TP | Multi-Gigabit Smart Switch with 8-port 2.5GBASE-T PoE, 2-port 10GBASE-T, and 2-port 10G SFP+ |
| DMS-1250-10SPL | Multi-Gigabit Smart Switch with 8-port 2.5GBASE-T PoE and 2-port 10G SFP+ |
| Optional SFP Transceivers | |
| DGS-712 | 1000BASE-T copper SFP transceiver |
| DEM-310GT | 1000BASE-LX, single-mode, 10 km |
| DEM-311GT | 1000BASE-SX, multi-mode, 550 m |
| DEM-312GT2 | 1000BASE-SX multi-mode, 2 km |
| DEM-314GT | 1000BASE-LHX single-mode, 50 km |
| DEM-315GT | 1000BASE-ZX single-mode, 80 km |
| DEM-330T | 1000BASE-BX-D single-mode, 10 km (TX-1550/RX-1310 nm) |
| DEM-330R | 1000BASE-BX-U single-mode, 10 km (TX-1310/RX-1550 nm) |
| DEM-331T | 1000BASE-BX-D single-mode, 40km (TX-1550/RX-1310 nm) |
| DEM-331R | 1000BASE-BX-U single-mode, 40 km (TX-1310/RX-1550 nm) |
| Optional SFP+ Transceivers | |
| DEM-410T ² | 10GBASE-T copper SFP+ transceiver, 30 m |
| DEM-431XT | 10GBASE-SR multi-mode SFP+ transceiver |
| DEM-432XT | 10GBASE-LR single-mode SFP+ transceiver |
| DEM-433XT | 10GBASE-ER single-mode, 40 km SFP+ transceiver |
| DEM-434XT | 10GBASE-ZR single-mode, 80 km SFP+ transceiver |
| DEM-435XT | 10GBASE-LRM multi-mode, 200 m SFP+ transceiver |
| DEM-436XT-BXD | 10GBASE-LR single-mode, 20 km (TX-1330/RX-1270 nm) |
| DEM-436XT-BXU | 10GBASE-LR single mode, 20 km (TX-1270/RX-1310 nm) |
| DAC Cables | |
| DEM-CB100S | 1 meter 10G 30AWG Passive SFP+ to SFP+ direct attach cable |
| DEM-CB300S | 3 meter 10G 30AWG Passive SFP+ to SFP+ direct attach cable |

¹ Available on PoE models only.

² The DEM-410T transceiver is only compatible with DMS-1250-10S, DMS-1250-10SP, and DMS-1250-12TP switches.

³ Console port is only available on the DMS-1250-10S, DMS-1250-10SP, and DMS-1250-12TP models.

Updated 12/12/2023