



# Partner Marketing Kit

**HT818**

*December, 2017*

# Agenda

---

About HT818 .....	3
Messaging Strategy .....	4
Datasheets .....	5
Marketing Assets .....	6

# About HT818

Built for users looking for a strong analog-to-VoIP converter, the HT818 is a powerful 8-port VoIP gateway with 8 FXS ports and an integrated Gigabit NAT router. It features Grandstream's market-leading SIP ATA/gateway technology with millions of units successfully deployed worldwide. This powerful gateway carries exceptional voice quality in various application environments, strong encryption with unique security certificate per unit, automated provisioning for volume deployment and device management, and outstanding network performance for enterprise use.

[French](#)

[Italian](#)

[Russian](#)

[German](#)

[Portuguese](#)

[Spanish](#)

# Messaging Strategy

HT818

<b>Tagline</b>	Powerful 8-port VoIP Gateway
<b>Subhead</b>	<i>Built for large deployments</i>
<b>What sets HT818 apart from competitors?</b>	Grandstream is the global market leader in ATAs, with millions of units successfully deployed around the globe, including by some of the biggest service providers worldwide. The HT818 was built for users who want to convert a big number of analog endpoints into VoIP. Bringing outstanding network performance with rich IP features, the HT818 is ideal for large environments seeking advanced VoIP features and functionality.
<b>Key Differentiators</b>	<ul style="list-style-type: none"><li>• Supports 2 SIP profiles and 8 FXS ports</li><li>• Supports dual Gigabit network ports</li><li>• High performance NAT router</li><li>• Automated provisioning options</li><li>• Fax-over-IP options</li><li>• Supports a wide range of caller ID formats</li><li>• Advanced telephony features</li></ul>

[French](#)

[Italian](#)

[Russian](#)

[German](#)

[Portuguese](#)

[Spanish](#)

# HT818 Datasheet



## Powerful 8 port FXS Gateway with Gigabit NAT Router HT818

Built for users looking for a strong analog-to-VoIP converter, the HT818 is a powerful 8-port VoIP gateway with 8 FXS ports and an integrated Gigabit NAT router. It features Grandstream's market-leading SIP ATA/gateway technology with millions of units successfully deployed worldwide. This powerful gateway carries exceptional voice quality in various application environments, strong encryption with unique security certificate per unit, automated provisioning for volume deployment and device management, and outstanding network performance for enterprise use.

### 8 LINES

Supports 2 SIP profiles and 8 FXS ports



Strong AES encryption with unique security certificate per unit



Automated & secure provisioning options using TR069



3-way voice conferencing per port



Exceptional voice quality with wide-band HD codec



Supports T.38 Fax for reliable Fax-over-IP



Supports dual Gigabit network ports



High performance NAT router

<b>Interfaces</b>	
<b>Telephone Interfaces</b>	Eight (8) RJ11 FXS ports
<b>Network Interface</b>	Two (2) 10/100/1000Mbps RJ45 ports
<b>LED Indicators</b>	POWER, LAN, WAN, PHONE1, PHONE2, PHONE3, PHONE4, PHONE5, PHONE6, PHONE7, PHONE8
<b>Factory Reset Button</b>	Yes
<b>Voice, Fax, Modem</b>	
<b>Telephony Features</b>	Caller ID display or block, call waiting, flash, blind or attended transfer, forward, hold, do not disturb, 3-way conference
<b>Voice Codecs</b>	G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.729A/B, G.726, iLBC, OPUS, dynamic jitter buffer, advanced line echo cancellation
<b>Fax over IP</b>	T.38 compliant Group 3 Fax Relay up to 14.4kbps and auto-switch to G.711 for Fax Pass-through
<b>Short/Long Haul Ring Load</b>	2 REN, up to 1km on 24AWG line
<b>Caller ID</b>	Bellcore Type 1 & 2, ETSI, BT, NTT, and DTMF-based CID
<b>Disconnect Methods</b>	Busy Tone, Polarity Reversal/Wink, Loop Current
<b>Signaling</b>	
<b>Network Protocols</b>	TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS, DHCP, NTP, TFTP, SSH, STUN, SIP (RFC3261), SIP over TCP/TLS, SRTP, TR.069
<b>QoS</b>	Layer 2 (802.1Q VLAN, SIP/RTSP 802.1p) and Layer 3 (ToS, DiffServ, MPLS)
<b>DTMF Method</b>	In-audio, RFC2833 and/or SIP INFO
<b>Provisioning and Control</b>	HTTP, HTTPS, SSH, TFTP, TR.069, secure and automated provisioning using AES encryption, syslog
<b>Security</b>	
<b>Media</b>	SRTP
<b>Control</b>	TLS/SIPS/HTTPS
<b>Management</b>	Syslog support, SSH, remote management using web browser
<b>Physical</b>	
<b>Universal Power Supply</b>	Input: 100-240VAC, 50-60Hz Output: 12V/1.5A
<b>Environmental</b>	Operational: 32o - 104oF or 0° - 40°C Storage: 14o - 140oF or -10° - 60°C Humidity: 10 - 90% Non-condensing
<b>Dimension and Weight</b>	(L)180mm*(W)120mm*(H)36mm 356g
<b>Compliance</b>	FCC/CE/RCM

[English datasheet](#)

[French datasheet](#)

[German datasheet](#)

[Italian datasheet](#)

[Portuguese datasheet](#)

[Russian datasheet](#)

[Spanish datasheet](#)

# Marketing Assets

1. [HT818 pictures](#)
2. [Feature icons](#)
3. [Social media banners](#)
4. [Web banners](#)
5. [Email banners](#)
6. Lifestyle Imagery Samples:  
[Option 1](#) , [Option 2](#) or [Option 3](#)