

USB Type-C 7-in-1 Hub

Bridge Devices, Expand Connections













1× SD/1× microSD 200 MB/s



Highlights





HDMI Ultra High-Definition Media Display



USB 3.0 5 Gbps SuperSpeed Data Transfer

Plug & Play For Various Operating Systems

٦P



Convenient & Stylish Self-Storage for Connector

Bridge Devices, Expand Connections





SD/microSD

UHS-I 200 MB/s **Dual-card Reading**



PD 3.0 Powerful 100W Fast Charging





Scratch Resistant Aluminum Alloy Case



Durable Design **Braided Cable**

TP-Link USB Type-C 7-in-1 Hub UH7020C

Specifications

Hardware

· Interface:

1× PD 3.0 100W Charging 2× USB 3.0 Type-A 5Gbps 1× USB 3.0 Type-C 5Gbps 1× HDMI 4K@60Hz 1×SD Card Port 1×microSD Card Port

- Connector:
 1× USB Type-C
- PD Input: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
- USB-C Connector Input: 5V/3A

Physical

- Dimension (W×D×H):
 5 × 1.57 × 0.48 in (127.2 × 40 × 12.2 mm)
- Case:
 Aluminum Alloy Case
- Cable:
 180mm Braided Cable
- Package Contents:
 1× UH7020C
 1× Quick Installation Guide



For more information, please visit

https://www.tp-link.com/products/details/?model=UH7020C_V1

or scan the QR code left

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders. ¹Port transmission specifications are the testing result conducted by TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a results of device conditions and environmental factors. [©]2025 TP-Link [©]2025 TP-Link

Others

Supported Systems:

Windows, Mac OS, iPad OS, iOS, Google Chrome OS, Linux OS, Android OS

· Plug & Play:

USB-C PD port, USB-C port, HDMI port, TF (microSD) card slot, SD card slot, USB-A ports. *The ports' actual performance may vary based on your host device specifications.

Certification: CE, FCC, RoHS, HDMI, BSMI

· Environment:

Operating Temperature: 0°C~40°C (32°F~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing