# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

### Supplier's name or trade mark: MI

Supplier's address: -

#### Model identifier: MJGJD01YL

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	USB Type C		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

# Product parameters

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	5	Energy efficiency class	G		
Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50°), in a wide	270 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500		
On-mode p expressed in W	ower (P <sub>on</sub> ),	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,40		
Networked stand for CLS, expres rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	95		
Outer	Height	448	Spectral power	See image		
dimensions	Width	23	distribution in the	in last page		
L		1		Page 1 /		

without [ separate control gear, lighting control parts and non- lighting control parts,	Depth	23	range 250 nm to 800 nm, at full-load	
if any (millimetre)			-	
Claim of equivaler	nt power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,380 0,366
Parameters for di	rectional light s	ources:		
Peak luminous int	ensity (cd)	310	Beam angle in degrees, or the range of beam angles that can be set	110
Parameters for LE	D and OLED lig	ht sources:		
R9 colour renderin	ng index value	50	Survival factor	0,90
the lumen mainte	nance factor	0,96		
(a), , not applicable.				

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

