



PoE Injector

This PoE Injector supports Gigabit speeds while offering 1 LAN port, 1 PoE port and output voltage of 48V 0.5A. The device includes an AC power adaptor which requires 24W maximum and offers one LED indicator to visually identify active use.

PoE Standard	No Detection – passive injector
Input Power	100-240VAC;50-60Hz 0.75A
PoE Output	Output: 48V0.5A
Power Consumption	24W max
RJ45 Pin Assignment & Polarity Powers	Pins 4/5(+), 7/8(-)
Data Rate	10/100/1000Mbps
MTBF	500K Hours
Safety Approval	UL/cUL,GS,CB,FCC,CE
Efficiency	VI
Standards	IEEE 802.3 10Base-T, IEEE 802.3U 100Base-TX, IEEE 802.3ab 1000Base-T
LED Indicator	AC power; PoE Active
Interface	1 "Data" In RJ-45 Ethernet Port 1 "Data+Power" Output RJ-45 Ethernet Port 1 AC Input Power socket
Environmental	
Operating Temperature	0 to +40
Storage Temperature	-40 to +70
Humidity	0 to +95 RH
Mechanical	
Device Weight	133g
Dimensions	97mm x 53.5mm x 33.5mm 114mm x 53.5mm x 67.5mm (including ear)